

P4CCS058



DESCRIPTION

- Connector cap for straight cable routing (Form A)
- Quick and intuitive assembly due to one-piece design
- Feature for zip-tie usage
- Robust design related to reliable clipping elements
- Improved Ergo usage
- Slim design for minimum space requirement
- Cable routing can be flexibly selected during installation - no rigid orientation
- Suitable for all available connector variants of the manufacturer

GENERAL INFORMATION

SAP Material No (Virgin Material)	88000006248
Material type (Virgin Material)	PA 6.6/6
SAP material number	88000008968
Material type (Recyclate)	PA 6.6
Colour description	black
Length A	64,8 mm
Height C	49,6 mm
Width B	17,6 mm
Number of poles	2
Outlet form	A

TECHNICAL PROPERTIES

Nominal width	
Weight	6,2 g
Chemical resistance	Alcohol, weak alkalis, solvents, fuels, mineral oils, grease/oils
Temperature resistance	-40°C up to +130°C
General Tolerance	UL94 HB
Water resistance	Supports IPX9K impermeability

PERFORMANCE INDICATOR

Assembly force	on request
Pull-off force	on request
Abzugskraft vom Stecker (-40°C) (Nm)	on request
Pull-off force Corrugated tube (N)	on request



Further details, sizes and designs:
<https://www.poeppelmann.com/en/k-tech/browse>

SUITABLE FOR

Manufacturer/ Connector family

Hirschmann HPS40-2 2+2

Connector no.807-655-501, 807-655-502, 807-655-503, 807-655-504,
807-655-507

CO₂ FOOTPRINT OF THE PRODUCT

Material type (Virgin Material)	PA 6.6/6
THG Virgin material total	47,70
Material type (Recyclate)	PA 6.6
Material description (Recyclate)	Pöppelmann I2022Fbk
THG PIR total	7,25
Saving	84,80%

Sum of all GHG emissions for the product:

Product carbon footprint consideration "cradle-to-gate" (Pöppelmann).

The estimation of the greenhouse gas footprint is based on different values and data with varying quality and accuracy. We are guided by DIN EN ISO 14067 and the GHG Protocol.

PACKAGING

Basic unit standard packaging

VPA per product carrier

ADVANTAGES

**SCHUTZ VOR STAUB
UND SCHMUTZ****OPTIMALE NUTZUNG
DES BAURAUMS****INTUITIVE MONTAGE****SCHUTZ DER LEITUNGEN****REDUZIERUNG VON
SCHWINGUNGEN****EINSATZ AUF ENGSTEM
RAUM**

Further details, sizes and designs:
<https://www.poeppelmann.com/en/k-tech/browse>

FURTHER INFORMATION

Customs item number 39269097
Production DE Germany



Further details, sizes and designs:
<https://www.poeppelmann.com/en/k-tech/browse>