

# P4CCR19

## DESCRIPTION



## GENERAL INFORMATION

SAP Material No (Virgin Material)	88000007625
Material type (Virgin Material)	PA 6.6
SAP material number	88000002790
Material type (Recyclate)	PA 6.6
Colour description	black
Length A	67,4 mm
Height C	32,7 mm
Width B	19,6 mm
Number of poles	10
Outlet form	B

## TECHNICAL PROPERTIES

Nominal width	7,5
Weight	3,7 g
Chemical resistance	Alcohol, weak alkalis, solvents, fuels, mineral oils, grease/oils
Temperature resistance	-40°C up to +130°C
General Tolerance	UL94 HB
Water resistance	

## PERFORMANCE INDICATOR

Assembly force	on request
Pull-off force	on request
Abzugskraft vom Stecker (-40°C) (Nm)	on request
Pull-off force Corrugated tube (N)	on request



Further details, sizes and designs:  
<https://www.poeppelmann.com/en/k-tech/browse>

## SUITABLE FOR

### Manufacturer/ Connector family

Yazaki RH Connector

### Connector no.

7283-8856-30

## CO<sub>2</sub> FOOTPRINT OF THE PRODUCT

Material type (Virgin Material)	PA 6.6
THG Virgin material total	24,26
Material type (Recyclate)	PA 6.6
Material description (Recyclate)	Pöppelmann I2022Fbk
THG PIR total	4,19
Saving	82,73%

Sum of all GHG emissions for the product:

Product carbon footprint consideration "cradle-to-gate" (Pöppelmann).

The estimation of the greenhouse gas footprint is based on different values and data with varying quality and accuracy. We are guided by DIN EN ISO 14067 and the GHG Protocol.

## PACKAGING

### Basic unit standard packaging

VPA per product carrier

## ADVANTAGES



SCHUTZ VOR STAUB  
UND SCHMUTZ



OPTIMALE NUTZUNG  
DES BAURAUMS



INTUITIVE MONTAGE



SCHUTZ DER LEITUNGEN



REDUZIERUNG VON  
SCHWINGUNGEN



EINSATZ AUF ENGSTEM  
RAUM

## FURTHER INFORMATION

### Customs item number

39269097

### Production DE

Germany



Further details, sizes and designs:  
<https://www.poeppelmann.com/en/k-tech/browse>