

1184564



DESCRIPTION

GENERAL INFORMATION

SAP Material No (Virgin Material)	11845640000
Material type (Virgin Material)	PA 6.6/6
SAP material number	-
Material type (Recyclate)	-
Colour description	black
Length A	59,2 mm
Height C	28 mm
Width B	31,6 mm
Number of poles	5
Outlet form	C

TECHNICAL PROPERTIES

Nominal width	7,5
Weight	4,3 g
Chemical resistance	Alcohol, weak alkalis, solvents, fuels, mineral oils, grease/oils
Temperature resistance	-40°C up to +130°C
General Tolerance	UL94 HB
Water resistance	Supports IPX9K impermeability

PERFORMANCE INDICATOR

Assembly force	on request
Pull-off force	on request
Abzugskraft vom Stecker (-40°C) (Nm)	on request
Pull-off force Corrugated tube (N)	on request



Further details, sizes and designs:
<https://www.poeppelmann.com/en/k-tech/browse>

SUITABLE FOR

Manufacturer/ Connector family		Connector no.
Kostal	MLK 1.2	09 4085 01, 09 4085 02, 09 4085 03, 09 4085 04, 09 4085 11, 09 4085 12, 09 4085 13, 09 4085 14, 09 4085 19, 09 4085 09
Kostal	MLK 1.2	09 4087 01, 09 4087 02, 09 4087 03, 09 4087 04, 09 4087 09, 09 4087 11, 09 4087 12, 09 4087 13, 09 4087 14, 09 4087 19
Kostal	MLK 1.2	09 4086 01, 09 4086 02, 09 4086 03, 09 4086 04, 09 4086 09, 09 4086 11, 09 4086 12, 09 4086 13, 09 4086 14, 09 4086 19, 09 4086 21, 09 4086 22, 09 4086 23, 09 4086 24, 09 4086 29, 09 4086 31, 09 4086 32, 09 4086 33, 09 4086 34, 09 4086 39
Tyco	MCON 1.2	1-1718806-1, 2-1718806-1, 3-1718806-1
Tyco	MCON 1.2	1-1670921-1, 2-1670921-1
Hirschmann	1.2 SealStar	805-123-551, 805-123-552, 805-123-572, 805-123-542, 805-123-541
Hirschmann	1.2 SealStar	872-860-521, 872-860-525, 872-860-526, 872-860-541, 872-860-546

CO₂ FOOTPRINT OF THE PRODUCT

Material type (Virgin Material)	PA 6.6/6
THG Virgin material total	32,18
Material type (Recyclate)	-
Material description (Recyclate)	-
THG PIR total	5,26
Saving	83,65%

Sum of all GHG emissions for the product:

Product carbon footprint consideration "cradle-to-gate" (Pöppelmann).

The estimation of the greenhouse gas footprint is based on different values and data with varying quality and accuracy. We are guided by DIN EN ISO 14067 and the GHG Protocol.

PACKAGING

Basic unit standard packaging	2.200
VPA per product carrier	12



Further details, sizes and designs:
<https://www.poeppelmann.com/en/k-tech/browse>

ADVANTAGES



SCHUTZ VOR STAUB
UND SCHMUTZ



OPTIMALE NUTZUNG
DES BAURAUMS



INTUITIVE MONTAGE



SCHUTZ DER LEITUNGEN



REDUZIERUNG VON
SCHWINGUNGEN



EINSATZ AUF ENGSTEM
RAUM

FURTHER INFORMATION

Customs item number 39269097
Production DE Germany



Further details, sizes and designs:
<https://www.poeppelmann.com/en/k-tech/browse>