

# P4CCC004



## DESCRIPTION

- Connector cap with straight cable outlet.
- Quick and easy assembly due to the one-piece design.
- Connector cap can be installed on both sides.
- High resilience due to clipping of the connector cap halves.

## GENERAL INFORMATION

SAP Material No (Virgin Material)	11872630000
Material type (Virgin Material)	PA 6.6/6
SAP material number	
Material type (Recyclate)	
Colour description	black
Length A	46 mm
Height C	25,6 mm
Width B	23,7 mm
Number of poles	4 / 6
Outlet form	B

## TECHNICAL PROPERTIES

Nominal width	7,5
Weight	3,7 g
Chemical resistance	Alcohol, weak alkalis, solvents, fuels, mineral oils, grease/oils
Temperature resistance	-40°C up to +130°C
General Tolerance	UL94 HB
Water resistance	Supports IPX9K impermeability

## PERFORMANCE INDICATOR

Assembly force	on request
Pull-off force	on request
Abzugskraft vom Stecker (-40°C) (Nm)	on request
Pull-off force Corrugated tube (N)	on request



Further details, sizes and designs:  
<https://www.poeppelmann.com/en/k-tech/browse>

## SUITABLE FOR

Manufacturer/ Connector family		Connector no.
TE Connectivity	HDSCS Group B	C-1703808, 1-1703808-1, 2-1703808-1, 3-1703808-1, 4-1703808-1
TE Connectivity	HDSCS Group B	C-1703820, 1-1703820-1, 2-1703820-1, 3-1703820-1, 4-1703820-1
TE Connectivity	HDSCS Group B	C-1703818, 1-1703818-1, 2-1703818-1, 3-1703818-1, 4-1703818-1
TE Connectivity	HDSCS Group B	C-1703773, 1-1703773-1, 2-1703773-1, 3-1703773-1, 4-1703773-1
TE Connectivity	HDSCS Group B	C-1418390, 1-1418390-1, 2-1418390-1, 3-1418390-1, 4-1418390-1, 5-1418390-1, 6-1418390-1
TE Connectivity	HDSCS Group B	C-1418469, 1-1418469-1, 2-1418469-1, 3-1418469-1, 4-1418469-1
Aptiv	CTCS XP	33308735, 33308962, 33308973, 33346867, 33347789, 33347791, 33347794, 33308731
Aptiv	CTCS XP	33308979, 33308980, 33308981, 33346866, 33347795, 33347798, 33347799, 33308978
Aptiv	CTCS XP	33308913, 33308914, 33308915, 33347886, 33347887, 33347888, 33347889, 33308912
Aptiv	CTCS XP	33308975, 33308976, 33308977, 33346865, 33346862, 33346860, 33346858, 33308974
Aptiv	CTCS XP	33308909, 33308910, 33308911, 33347865, 33347867, 33347868, 33347869, 33308982
Aptiv	CTCS XP	33308963, 33308964, 33308965, 33346852, 33347848, 33347849, 33347850, 33308961
Yazaki	Y-NEWT	7298-1795-40, 7298-1796-60, 7298-1797-90, 7298-1794-30
Yazaki	Y-NEWT	7298-1799-40, 7298-1800-60, 7298-1801-90, 7298-1798-30

## CO<sub>2</sub> FOOTPRINT OF THE PRODUCT

<b>Material type (Virgin Material)</b>	PA 6.6/6
<b>THG Virgin material total</b>	24,55
<b>Material type (Recyclate)</b>	
<b>Material description (Recyclate)</b>	
<b>THG PIR total</b>	4,48
<b>Saving</b>	81,75%

Sum of all GHG emissions for the product:

Product carbon footprint consideration "cradle-to-gate" (Pöppelmann).

The estimation of the greenhouse gas footprint is based on different values and data with varying quality and accuracy. We are guided by DIN EN ISO 14067 and the GHG Protocol.



Further details, sizes and designs:  
<https://www.poeppelmann.com/en/k-tech/browse>

---

## PACKAGING

---

Basic unit standard packaging	2.000
VPA per product carrier	12

---

## ADVANTAGES

---



SCHUTZ VOR STAUB  
UND SCHMUTZ



OPTIMALE NUTZUNG  
DES BAURAUMS



INTUITIVE MONTAGE



SCHUTZ DER LEITUNGEN



REDUZIERUNG VON  
SCHWINGUNGEN



EINSATZ AUF ENGSTEM  
RAUM

---

## FURTHER INFORMATION

---

Customs item number	39269097
Production DE	Germany



Further details, sizes and designs:  
<https://www.poeppelmann.com/en/k-tech/browse>