

# P4CCL030



## DESCRIPTION

- Connector cap for straight cable routing (Form A)
- Quick and intuitive assembly due to one-piece design
- Non orientated assembly
- Robust design related to reliable clipping elements
- Feature for zip-tie usage
- Integrated pre-assembly for corrugated tube

## GENERAL INFORMATION

<b>SAP Material No (Virgin Material)</b>	88000007328
<b>Material type (Virgin Material)</b>	PA 6.6
<b>SAP material number</b>	88000001601
<b>Material type (Recyclate)</b>	PA 6.6
<b>Colour description</b>	black
<b>Length A</b>	65,2 mm
<b>Height C</b>	34,3 mm
<b>Width B</b>	11,3 mm
<b>Number of poles</b>	4
<b>Outlet form</b>	A

## TECHNICAL PROPERTIES

<b>Nominal width</b>	7,5
<b>Weight</b>	2,9 g
<b>Chemical resistance</b>	Alcohol, weak alkalis, solvents, fuels, mineral oils, grease/oils
<b>Temperature resistance</b>	-40°C up to +130°C
<b>General Tolerance</b>	UL94 HB
<b>Water resistance</b>	Supports IPX9K impermeability

## PERFORMANCE INDICATOR

<b>Assembly force</b>	on request
<b>Pull-off force</b>	on request
<b>Abzugskraft vom Stecker (-40°C) (Nm)</b>	on request
<b>Pull-off force Corrugated tube (N)</b>	on request



Further details, sizes and designs:  
<https://www.poeppelmann.com/en/k-tech/browse>

## SUITABLE FOR

Manufacturer/ Connector family		Connector no.
Tyco	AMP Superseal 1.5	282088-1, 282088-2, 282088-3
Tyco	AMP Superseal 1.5	1745101-1

## CO<sub>2</sub> FOOTPRINT OF THE PRODUCT

Material type (Virgin Material)	PA 6.6
THG Virgin material total	16,76
Material type (Recyclate)	PA 6.6
Material description (Recyclate)	Pöppelmann I2022Fbk
THG PIR total	3,49
Saving	79,18%

Sum of all GHG emissions for the product:

Product carbon footprint consideration "cradle-to-gate" (Pöppelmann).

The estimation of the greenhouse gas footprint is based on different values and data with varying quality and accuracy. We are guided by DIN EN ISO 14067 and the GHG Protocol.

## PACKAGING

Basic unit standard packaging	2.000
VPA per product carrier	12

## ADVANTAGES



SCHUTZ VOR STAUB  
UND SCHMUTZ



OPTIMALE NUTZUNG  
DES BAURAUMS



INTUITIVE MONTAGE



SCHUTZ DER LEITUNGEN



REDUZIERUNG VON  
SCHWINGUNGEN



EINSATZ AUF ENGSTEM  
RAUM



Further details, sizes and designs:  
<https://www.poeppelmann.com/en/k-tech/browse>

FURTHER INFORMATION

---

Customs item number      39269097  
Production DE              Germany



Further details, sizes and designs:  
<https://www.poeppelmann.com/en/k-tech/browse>