

P4CDR033



DESCRIPTION

- Delete cap matching to Tyco GET064 female connectors
- Long-term protection of the female connector pins against failure
- Secure installation in the connector housing thanks to lateral latching elements
- Water resistance according to IPX9k
- The cap is independent of connector coding



GENERAL INFORMATION

SAP Material No (Virgin Material)	88000007567
Material type (Virgin Material)	PBT
SAP material number	
Material type (Recyclate)	
Colour description	black
Length A	19,5 mm
Height C	20,2 mm
Width B	14,8 mm
Number of poles	4
Outlet form	Blindkappe

TECHNICAL PROPERTIES

Nominal width	
Weight	1,6 g
Chemical resistance	Alcohol, weak alkalis, solvents, fuels, mineral oils, grease/oils
Temperature resistance	-40°C up to +130°C
General Tolerance	UL94 HB
Water resistance	

PERFORMANCE INDICATOR

Assembly force	on request
Pull-off force	on request
Abzugskraft vom Stecker (-40°C) (Nm)	on request
Pull-off force Corrugated tube (N)	on request



Further details, sizes and designs:
<https://www.poeppelmann.com/en/k-tech/browse>

SUITABLE FOR

CO₂ FOOTPRINT OF THE PRODUCT

Material type (Virgin Material)	PBT
THG Virgin material total	8,34
Material type (Recyclate)	
Material description (Recyclate)	
THG PIR total	1,74
Saving	79,14%

Sum of all GHG emissions for the product:

Product carbon footprint consideration "cradle-to-gate" (Pöppelmann).

The estimation of the greenhouse gas footprint is based on different values and data with varying quality and accuracy. We are guided by DIN EN ISO 14067 and the GHG Protocol.

PACKAGING

Basic unit standard packaging
VPA per product carrier

ADVANTAGES



SCHUTZ VOR STAUB
UND SCHMUTZ



OPTIMALE NUTZUNG
DES BAURAUMS



INTUITIVE MONTAGE



SCHUTZ DER LEITUNGEN



REDUZIERUNG VON
SCHWINGUNGEN



EINSATZ AUF ENGSTEM
RAUM

FURTHER INFORMATION

Customs item number 39269097
Production DE Germany



Further details, sizes and designs:
<https://www.poeppelmann.com/en/k-tech/browse>